

蝸輪-單段系統- MPHVS

尺寸表 DIMENSION *in millimeter

型號 Size	減速比 Ratio	A	AB	BB	CC	D	DD	E	E1	E2	E3	F	G	Z	馬力 Power		入力孔 Input Bore			入力法蘭 Input Adapter					出力軸 Output Shaft				重量 (Kg)	油量 (l)
															HP	KW	U	T	V	PA	PB	PC	PD	PK	LS	S	D	W×Y×LK		
40		140	78.5	84	40	129	45	70	78	99	207	102	10	10	0.25	0.2	11	4	12.5	160	130	110	5	M8	35	15	17	5x5x25	5.6	0.18
50		155	85	95	50	147	52	90	92	112	236	115	14	11	0.25	0.2	11	4	12.5	160	130	110	5	M8	40	17	19	5x5x35	6.8	0.31
60		180	102	110	60	168	58	100	130	130	265	127	15	11	0.25	0.2	11	4	12.5	160	130	110	5	M8	50	22	25	7x7x45	8.4	0.44
															0.5	0.4	14	5	16											
70	(特殊) 1:5	212	117	130	70	198	68	120	120	155	305	156	20	15	0.5	0.4	14	5	16	160	130	110	5	M8	60	28	31	7x7x55	15.3	0.70
															1	0.75	19	6	21.5	200	165	130	5	M10						
80	(標準) 1:10	233	129	140	80	215	75	140	132	180	342	176	20	15	1	0.75	19	6	21.5	200	165	130	5	M10	65	32	35	10x8x60	21.0	0.99
	1:15														2	1.5	24	8	27											
	1:20														2	1.5	24	8	27	200	165	130	5	M10						
100	1:30	295	160	170	100	260	90	190	155	215	400	227	20	15	3	2.2	28	8	31	250	215	180	5	M12	75	38	41	10x8x65	41.0	1.87
	1:40														3	2.2	28	8	31											
	1:50														3	2.2	28	8	31	250	215	180	5	M12	85	45	48	12x8x70	61.0	4.10
120	1:60	334	175	190	120	295	105	220	200	260	505	264	25	18	5	3.7	28	8	31											
															5	3.7	28	8	31	250	215	180	5	M12						
135		380	202	210	135	323	113	260	235	290	570	304	35	18	7.5	5.5	38	10	41	300	265	230	5	M12	95	55	60	15x10x80	83.0	4.40
155		437	232	252	155	387	135	280	217	310	583	340	35	20	7.5	5.5	38	10	41	300	265	230	5	M12	110	60	65	15x10x95	104	7.00
175		477	252	262	175	422	160	320	290	365	715	380	35	20	10	7.5	38	10	41	300	265	230	5	M12	110	65	69	18x11x95	150	8.00

NOTE: