

蝸輪-雙段系統- PAW

尺寸表 DIMENSION *in millimeter																				
型號 Size	減速比 Ratio		A	AA	AB	AC	B	BB	BL	CC	E	F	H	HL	LL	M	N	SG	G	Z
60	1:100 1:150 1:200 1:300 1:400 1:500 1:600 1:800 1:900	1:1000 1:1200 1:1500 1:1600 1:1800 1:2000 1:2400 1:2500 1:3000 1:3600	218	88	100	43	198	110	182	60	105	120	210	150	90	130	150	32	18	11
70			260.5	96	120.5	45	226	130	215	70	115	150	240	175	105	150	190	40	20	15
80			285	105	132	49	245	140	250	80	135	180	270	200	120	170	220	50	24	15
100			353	120	163	55	290	170	310	100	155	220	340	250	150	190	270	60	25	15
120			409.5	140	187	64	310	190	370	120	180	260	405	300	180	230	320	70	30	18
135			465	160	216.5	71	370	210	450	135	200	290	455	350	215	250	350	80	35	18
155			558.5	190	267	84	442	252	490	155	220	320	490	390	235	280	390	100	35	20
175			618	230	302	103	492	262	555	175	250	350	565	435	260	310	420	120	40	20
200			670	260	322	110	565	305	625	200	290	350	625	490	290	350	420	135	42	22

尺寸表 DIMENSION *in millimeter															
型號 Size	減速比 Ratio		馬力 HP		入力軸 Input Shaft				出力軸 Output Shaft				重量 (Kg)	油量 (l)	
			1/100~ 1/900	1/1000~ 1/3600	HS	U	d	TxVxHK	LS	S	D	WxYxLK		1st	2nd
60	1:100 1:150 1:200 1:300 1:400 1:500 1:600 1:800 1:900	1:1000 1:1200 1:1500 1:1600 1:1800 1:2000 1:2400 1:2500 1:3000 1:3600	1/16	*	28	12	13.5	4x4x20	50	22	25	7x7x45	10.9	0.16	0.33
70			1/8	1/16	28	12	13.5	4x4x25	60	28	31	7x7x55	16	0.17	0.50
80			1/4	1/8	30	12	13.5	4x4x25	65	32	35	10x8x60	22	0.31	0.77
100			1/2	1/4	40	15	17	5x5x35	75	38	41	10x8x65	36	0.44	1.50
120			1	1/2	40	18	20	5x5x35	85	45	48	12x8x70	63	0.70	2.35
135			2	1	50	22	25	7x7x45	95	55	60	15x10x80	88	1.00	3.20
155			3	2	50	25	28	7x7x45	110	60	65	15x10x95	129	1.87	4.00
175			5	3	65	30	33	7x7x55	110	65	69	18x11x95	186	4.10	5.70
200			7.5	5	75	35	38	10x8x65	125	70	74.5	20x12x110	245	4.40	7.90