

蝸輪-雙段系統- PAWE

尺寸表 DIMENSION *in millimeter

型號 Size	減速比 Ratio	A	AA	AB	AC	B	BB	BL	CC	E	F	H	HL	LL	M	N	SC	G	Z
60	1:100 1:150 1:200 1:300 1:400 1:500 1:600 1:800 1:900 1:3600	218	85	100	43	195	110	182	60	105	120	210	150	90	130	150	32	18	11
70		260.5	78.5	120.5	45	209	130	215	70	115	150	240	175	105	150	190	40	20	15
80		285	85	132	49	225	140	250	80	135	180	270	200	120	170	220	50	24	15
100		353	102	163	55	272	170	310	100	155	220	340	250	150	190	270	60	25	15
120		409.5	117	187	64	307	190	370	120	180	260	405	300	180	230	320	70	30	18
135		465	129	216.5	71	339	210	450	135	200	290	455	350	215	250	350	80	30	18
155		558.5	160	267	84	412	252	490	155	220	320	490	390	235	280	390	100	35	20
175		618	175	302	103	437	262	555	175	250	350	565	435	260	310	420	120	40	20
200		670	201	322	110	506	305	625	200	290	350	625	490	290	350	420	135	42	22

尺寸表 DIMENSION *in millimeter

尺寸表 DIMENSION *in millimeter																			
型號 Size	減速比 Ratio		入力孔 Input Bore			入力軸 Input Shaft					出力軸 Output Shaft				馬力 HP		重量 (Kg)	油量 (l)	
			U	T	V	PA	PB	PC	PD	PK	LS	S	D	WxYxLK	HP	Kw		1st	2nd
60	1:100 1:150 1:200 1:300 1:400 1:500 1:600 1:800 1:900 1:3000 1:3600		11	4	12.5	160	130	110	5	M8	50	22	25	7x7x45	0.25	0.2	11.7	0.16	0.33
70			11	4	12.5	160	130	110	5	M8	60	28	31	7x7x55	0.25	0.2	17	0.17	0.50
80			11	4	12.5	160	130	110	5	M8	65	32	35	10x8x60	0.25	0.2	23	0.31	0.77
100			11	4	12.5	160	130	110	5	M8	75	38	41	10x8x65	0.25	0.2	36	0.44	1.50
			14	5	16	160	130	110	5	M8					0.5	0.4			
120			14	5	16	160	130	110	5	M8	85	45	48	12x8x70	0.5	0.4	64	0.70	2.35
			19	6	21.5	200	165	130	5	M10					1	0.75			
			19	6	21.5	200	165	130	5	M10					1	0.75			
135			19	6	21.5	200	165	130	5	M10	95	55	60	15x10x80	2	1.5	90	1.00	3.20
			24	8	27	200	165	130	5	M10					2	1.5			
			24	8	27	200	165	130	5	M10					2	1.5			
155			24	8	27	200	165	130	5	M10	110	60	65	15x10x95	3	2.2	129	1.87	4.00
			28	8	31	250	215	180	5	M12					3	2.2			
175			28	8	31	250	215	180	5	M12	110	65	69	18x11x95	5	3.7	189	4.10	5.70
			28	8	31	250	215	180	5	M12					5	3.7			
200	28	8	31	250	215	180	5	M12	125	70	74.5	20x12x110	7.5	5.5	248	4.40	7.90		
	38	10	41	300	265	230	5	M12					7.5	5.5					