

蝸輪-雙段系統- PBWE

尺寸表 DIMENSION *in millimeter

型號 Size	減速比 Ratio	A	AA	AB	AC	B	BB	BL	CC	E	F	H	HL	LL	M	N	SC	G	Z
60	1:100 1:150 1:200 1:300 1:400 1:500 1:600 1:800 1:900 1:3600	218	85	100	43	195	110	92	60	105	120	210	60	120	130	150	32	18	11
70		260.5	78.5	120.5	45	209	130	110	70	115	150	240	70	140	150	190	40	20	15
80		285	85	132	49	225	140	130	80	135	180	270	80	160	170	220	50	24	15
100		353	102	163	55	272	170	160	100	155	220	340	100	200	190	270	60	25	15
120		409.5	117	187	64	307	190	190	120	180	260	405	120	240	230	320	70	30	18
135		465	129	216.5	71	339	20	215	135	200	290	455	135	270	250	350	80	30	18
155		558.5	160	267	84	412	252	235	155	220	320	490	135	290	280	390	100	35	20
175		618	175	302	103	437	262	280	175	250	350	565	160	335	310	420	120	40	20
200		670	201	322	110	506	305	325	200	290	350	625	175	375	350	420	135	42	20
225		735	201	355	110	536	335	315	225	330	390	705	190	415	410	470	135	40	27

尺寸表 DIMENSION *in millimeter

尺寸表 DIMENSION *in millimeter																			
型號 Size	減速比 Ratio		入力孔 Input Bore			入力軸 Input Shaft					出力軸 Output Shaft				馬力 HP		重量 (Kg)	油量 (l)	
			U	T	V	PA	PB	PC	PD	PK	LS	S	D	WxYxLK	HP	Kw		1st	2nd
60	1:100 1:150 1:200 1:300 1:400 1:500 1:600 1:800 1:900 1:3600	1:1000 1:1200 1:1500 1:1600 1:1800 1:2000 1:2400 1:2500 1:3000 1:3600	11	4	12.5	160	130	110	5	M8	50	22	25	7x7x45	0.25	0.2	11.7	0.16	0.33
70			11	4	12.5	160	130	110	5	M8	60	28	31	7x7x55	0.25	0.2	17	0.17	0.50
80			11	4	12.5	160	130	110	5	M8	65	32	35	10x8x60	0.25	0.2	13	0.13	0.77
100			11	4	12.5	160	130	110	5	M8	75	38	41	10x8x65	0.25	0.2	36	0.44	1.50
			14	5	16	160	130	110	5	M8					0.5	0.4			
120			14	5	16	160	130	110	5	M8	85	45	48	12x8x70	0.5	0.4	64	0.70	2.35
			19	6	21.5	200	165	130	5	M10					1	0.75			
135			19	6	21.5	200	165	130	5	M10	95	55	60	15x10x80	1	0.75	90	1.00	3.20
			24	8	27	200	165	130	5	M10					2	1.5			
155			24	8	27	200	165	130	5	M10	110	60	65	15x10x95	2	1.5	129	1.87	4.00
			28	8	31	250	215	180	5	M12					3	2.2			
175			28	8	31	250	215	180	5	M12	110	65	69	18x11x95	3	2.2	189	4.10	5.70
			28	8	31	250	215	180	5	M12					5	3.7			
200			28	8	31	250	215	180	5	M12	125	70	74.5	20x12x110	5	3.7	248	4.40	7.90
			38	10	41	300	265	230	5	M12					7.5	5.5			
225					38	10	41	300	265	230	5	M12	140	80	84.5	20x12x105	7.5	5.5	267