

蝸輪-雙段系統- PVWE

配對法	60x32	70x40	80x50	100x60	120x70	135x80	155x100	175x120	200x135	225x135
-----	-------	-------	-------	--------	--------	--------	---------	---------	---------	---------

尺寸表 DIMENSION *in millimeter

型號 Size	減速比 Ratio	A	AA	AB	AC	B	BB	BC	BL	C	CC	E1	E2	F	M	N	SC	G	Z
60		218	85	100	43	165	110	55	87	123	60	105	120	100	260	126	32	18	11
70		260.5	78.5	120.5	45	195	130	65	105	140	70	120	135	120	295	158	40	20	15
80		285	85	132	49	210	140	70	120	150	80	130	150	140	320	176	50	24	15
100		353	102	163	55	260	170	90	150	175	100	155	180	190	375	226	60	25	15
120		409.5	117	187	64	290	190	100	170	210	120	185	215	220	450	268	70	30	18
135		465	129	216.5	71	320	210	110	190	235	135	210	235	260	495	306	80	35	18
155		558.5	160	267	84	392	252	140	240	170	155	145	265	290	456	336	100	35	20
175		618	175	302	103	412	262	150	270	202	175	167	293	320	516	380	120	40	20
200		670	201	322	110	480	305	175	310	255	200	*		450	580	510	135	42	22
225		735	201	355	110	525	335	190	325	374	225	*		510	664	580	135	40	27

尺寸表 DIMENSION *in millimeter

型號 Size	減速比 Ratio	入力孔 Input Bore			入力軸 Input Shaft					出力軸 Output Shaft				馬力 HP		重量 (Kg)	油量 (l)	
		U	T	V	PA	PB	PC	PD	PK	LS	S	D	WxYxLK	HP	Kw		1st	2nd
60		11	4	12.5	160	130	110	5	M8	50	22	25	7x7x45	0.25	0.2	11.7	0.16	0.66
70		11	4	12.5	160	130	110	5	M8	60	28	31	7x7x55	0.25	0.2	17	0.17	1.17
80		11	4	12.5	160	130	110	5	M8	65	32	35	10x8x60	0.25	0.2	23	0.31	1.49
100	1:100	11	4	12.5	160	130	110	5	M8	75	38	41	10x8x65	0.25	0.2	36	0.44	2.95
	1:150	14	5	16	160	130	110	5	M8					0.5	0.4			
120	1:200	14	5	16	160	130	110	5	M8	85	45	48	12x8x70	0.5	0.4	64	0.70	5.00
	1:300	19	6	21.5	200	165	130	5	M10					1	0.75			
135	1:400	19	6	21.5	200	165	130	5	M10	95	55	60	15x10x80	1	0.75	90	1.00	7.20
	1:500	24	8	27	200	165	130	5	M10					2	1.5			
155	1:600	24	8	27	200	165	130	5	M10	110	60	65	15x10x95	2	1.5	129	1.87	8.30
	1:800	28	8	31	250	215	180	5	M12					3	2.2			
175	1:900	28	8	31	250	215	180	5	M12	110	65	69	18x11x95	3	2.2	189	4.10	12.1
		28	8	31	250	215	180	5	M12					5	3.7			
200		28	8	31	250	215	180	5	M12	125	70	74.5	20x12x110	5	3.7	248	4.40	17.0
		38	10	41	300	265	230	5	M12					7.5	5.5			
225		38	10	41	300	265	230	5	M12	140	80	84.5	20x12x105	7.5	5.5	267	4.40	17.1